

Premium Series Portable Power Station

For Every Power-Packed Adventure



Faster Charging

- -Ready to go within **1 hour** with AC Turbo Charging or PV charging
- -Tap into abundant energy of the sun through efficient PV charging.

More Compact & Powerful

-High-density LFP battery cells for impressive capacity -Lifting Power for high-wattage resistive loads like hair dryers, electric kettles, etc.

Longer Lifespan

-Reliable LFP batteries and intelligent BMS (Battery Management System) provide optimal performance and up to 10 years of lifespan.

Higher Scalability


-Modular design allows for flexible capacity ranging from 1.8kWh to 10kWh, and up to 8 tailored solutions to cater to your unique power requirements.

Smarter Control


-With the intuitive **BLUETTI App**, you can monitor your power status in real time and customize your setup effortlessly, simply manage energy in the palm of your hand.

Dynamic Design

-The Premium series products come in vibrant orange, embodying warmth, hope, and the full spirit of energy.















| AC2P | AC60P |
|--|--|
| 230.4Wh | 504Wh (Expandable) |
| 300W (Lifting Power 600W for resistive loads) | 600W (Lifting Power 1,200W for resistive loads) |
| 1* AC 2* USB-A 3.6 kg / 7.9 lbs | Image: Second |
| AC70P | AC180P |
| 864Wh (Expandable) | 1,440Wh |
| 1,000W (Lifting Power 2,000W for resistive loads) | 1,800W (Lifting Power 2,700W for resistive loads) |
| Image: Constraint of the state of | Image: state stat |
| AC240P | AC200P L |
| 1,843Wh (Expandable) | 2,304Wh (Expandable) |
| 2,400W (Lifting Power 3,600W for resistive loads) | 2,400W (Lifting Power 3,600W for resistive loads) |
| Image: Constraint of the state of | Image: Second system Image: Se |

| Applications | | Devices | AC2P | AC60P | AC70P | AC180P | AC240P | AC200P L |
|--------------|-----|-----------------------------|------------|------------|------------|------------|------------|------------|
| RV & Outdoor | _ | Phone (IOWh) | 11 Times | 25 Times | 43 Times | 72 Times | 92 Times | 116 Times |
| _ | | Portable Fridge (65W) | 2.6 Hours | 5.4 Hours | 8.6 Hours | 14.4 Hours | 19.1 Hours | 23.9 Hours |
| | | Laptop (70Wh) | 2 Times | 4 Times | 7 Times | 11 Times | 14 Times | 18 Times |
| | | Coffee Maker (1,500W) | - | - | - | 0.8 Hours | 1.0 Hour | 1.2 Hours |
| Home Backup | | WiFi Router (7W) | 12.7 Hours | 23.7 Hours | 31.4 Hours | 52.4 Hours | 77.6 Hours | 97.0 Hours |
| | | TV (60W) | 2.3 Hours | 5.8 Hours | 9.2 Hours | 15.4 Hours | 20.5 Hours | 25.6 Hours |
| | 0* | Refrigerator (100W) | 1.7 Hours | 3.7 Hours | 6.0 Hours | 10.0 Hours | 13.2 Hours | 16.5 Hours |
| Workshop | | Blender (1,400W) | - | - | - | 0.8 Hours | 1.0 Hour | 1.3 Hours |
| | - Ţ | Electric Hammer (1,000W) | - | - | - | 1.1 Hours | 1.4 Hours | 1.8 Hours |
| | | Circular Saw (1,800W) | - | - | - | 0.6 Hours | 0.8 Hours | 1.0 Hour |

Note: For reference only



Power/W



Premium Series Datasheet

| | | | | es Dala | 3511661 | |
|--|---|---|---|---|---|--|
| | | | Power S | tation | | |
| | | | AC70P | | AC240P | AC200P L |
| AC Outlets | | | US/JP 💽 EU 💶 | UK 🚹 AU 🚺 SA 🛄 | CN | |
| Battery | | | Li | FePO ₄ | | |
| Capacity | 230.4Wh | 504Wh | 864Wh | 1,440Wh | 1,843Wh | 2,304Wh |
| Expandable Capacity | / | 2,116Wh (With 2 x B80P) | power bank mode 1,670Wh (With 1 x B80P) | power bank mode 2,246Wh (With 1 x B80P) | 10.443Wh (With 4 x B210P) | 6,604Wh (With 2 x B210P) |
| Life Cycles | 3,000+ | 3,000+ | 3,000+ | 3,500+ | 3,500+ | 3,500+ |
| Output Power | 300W | 600W | 1,000W | 1,800W | 2,400W | 2,400W |
| Lifting Power | 600W | 1,200W | 2,000W | 2,700W | 3,600W | 3,600W |
| PV Input | 12V~28V, 200W Max. | 12V~28V, 200W Max. | 12V~58V, 500W Max. | 12V~60V, 500W Max. | 11V~60V, 1,200W Max. | 12V~145V, 1,200W Max. |
| Charging Time | AC: 1.4 H (270W Max.) Solar: 1.5 H (200W Max.) Car: 1.5 H (200W Max.) Generator: 1.4 H (270W Max.) | AC: 1.3 H (600W Max.) Solar: 3 H (200W Max.) Car: 3 H (200W Max.) Generator: 1.3 H (600W Max.) | AC: 1.5 H (950W Max.) Solar: 2.2 H (500W Max.) Car: 4.8 H (200W Max.) Generator: 1.5 H (950W Max.) B300 Expansion Battery: 2.2 H (500W Max.) | AC: 1.5 H (1,440W Max.) Solar: 3.3 H (500W Max.) Car: 7.2 H (200W Max.) Generator: 1.5 H (1,440W Max.) | AC: 1.2 H (2,400W Max.) Solar: 1.8 H (1,200W Max.) Car: 9.2 H (200W Max.) Generator: 1.2 H (2,400W Max.) | AC: 1.5 H (2,400W Max.) Solar: 2.8 H (1,200W Max.) Car: 12.5 H (200W Max.) Generator: 2 H (2,000W Max.) Lead-acid Battery: 12.5 H (200W Max.) |
| Total Outlets | 5 | 7 | 8 | 9 | 10 | 12 |
| AC Outlets 220V-230V (CN/EU/UK/AU) | 1 | 2 | 2 | 2 | 4 | 4 |
| Bidirectional Inverter | | | | | | \checkmark |
| MPPT | \checkmark | \checkmark | | \checkmark | | \checkmark |
| UPS | \checkmark | \checkmark | | | | \checkmark |
| Арр | \checkmark | | \checkmark | | | \checkmark |
| IP Grade | 1 | IP65 | / | / | IP65 | / |
| Weight | 3.6 kg (7.9 lbs) | 9.6kg(21.16lbs) | 10.7 kg (23.6 lbs) | 17.0 kg (37.5 lbs) | 33.0 kg (72.0 lbs) | 28.3 kg (62.4 lbs) |
| Dimensions (L × W × H) | 250 × 150 × 180 mm (9.8 × 5.9 × 7.1 in) | 290 × 205 × 234 mm (11.4 × 8.1 × 9.2 in) | 314 × 210 × 256 mm (12.4 × 8.2 × 10.1 in) | 340 × 247 × 317 mm (13.4 × 9.7 × 12.5 in) | 420 × 294 × 410 mm (16.5 × 11.6 × 16.1 in) | 420 × 280 × 367 mm (16.5 × 11.0 × 14.4 in) |
| SKU | P-AC2P-UK-GY-BL-010 | P-AC60P-UK-GY-BL | P-AC70P-UK-GY-BL-010 | P-AC180P-UK-GY-BL | P-AC240P-UK-GY-BL | P-AC200P L-UK-GY-BL |
| Warranty | 5 Years | 6 Years | 5 Years | 5 Years | 6 Years | 5 Years |
| EAN | 6970991294549 | 6970991292965 | 6970991294242 | 6970991292903 | 6970991294884 | 6970991294761 |

Premium Series Datasheet

| | | Solar | Panel | | Expansion | on Battery | | | |
|--------------------------------|--|--|--|---|---------------------------|--|---|--|--|
| | PV120 | PV200 | PV350 PV420 | | | B80P | B210P | | |
| | | | | | | BLUETTI | | | |
| Power | 120W | 200W | 350W | 420W | Battery | LiFePO4 | | | |
| Cell Type | | Monocrys | stalline Silicon | | Capacity | 806Wh 2,150Wh | | | |
| Cell Efficiency | | Upt | 0 23.4% | | Life Cycles | 3,000+ | 3,500+ | | |
| Voltage at Max. Power (Vmp) | 19.6 V | 20.5 V | 37.5 V | 36.6 V | | AC Adapter: 4.5 H (200W Max.) | AC Adapter: 4.8 H (470W Ma: Solar: 4.5 H (500W Ma: Car: 10 H (200W Max | | |
| Current at Max. Power (Imp) | 6.1A | 9.7 A | 9.2 A | 11.5 A | Charging Time | Solar: 4.5 H (200W Max.) Car: 4.5 H (200W Max.) | | | |
| Open Circuit Voltage (Voc) | 24.4 V | 26.1V | 46.5 V | 44.3 V | Total Outlets | 3 | | | |
| Short Circuit Current (Isc) | 6.43 A | 10.3 A | 10.8 A | 12.2 A | Pass-through Charging | \checkmark | | | |
| Weight | 5.7 kg (12.6 lbs) | 7.3 kg (16.1 lbs) | 13.9 kg (30.6 lbs) | 14.0 kg (30.8 lbs) | IP Grade | IP65 | IP65 | | |
| | Unfolded: 533 × 1652 mm (21.0 × 65.0 in) | Unfolded: 590 × 2265 mm (23.2 × 89.2 in) | Unfolded: 905 x 2400 mm (35.6 x 94.4 in) | Unfolded: 2675 x 975 mm (105.3 x 38.3 in) | Weight | 9.9 kg (21.8 lbs) | 27.9 kg (61.5 lb | | |
| Dimensions | Folded: 533 × 470 mm (21.0 × 18.5 in) | Folded: 590 × 600 mm (23.2 × 24.8 in) | Folded: 905 x 613 x 65 mm (35.6 x 24.1 x 2.5 in) | Folded: 975× 660 × 45 mm (38.3 × 25.9 × 1.7 in) | Dimensions (L × W × H) | 290 × 207× 204 mm (11.4 × 8.2 × 8.0 in) | 417 × 282 × 270 r (16.4 × 11.1 × 10.6 | | |
| Compatibility | All BLUETT Power S | | BLUETTI AC70P/AC180P/ AC240P/AC200P L | | Compatibility | BLUETTI AC60P | BLUETTI AC200P L / / | | |
| Warranty | | 12 M | onths | | Warranty | 6 Ye | ears | | |
| SKU | PV120-UK-BK-BL-01 | PV200-UK-BK-BL-01 | PV350-UK-BK-BL-01 | PV420-UK-GY-BL-00 | SKU | P-B80P-UK-GY-BL | P-B210P-UK-G` | | |
| EAN | 6970991292101 | 6970991292118 | 6970991292125 | 6970991291845 | EAN | 6970991293023 | 69709912949 | | |

PV Optimizer (D40)

| D40 DC-DC Battery Charger | Charging Power | Max. Output Current | Max. Output Voltage | DC Input | IP Grade | Weight | Dimensions (L × W × H) | Compatibility | SKU | EAN |
|------------------------------|-------------------|---|--|--|-------------|----------------|---|---------------------|-----|-----|
| | 400W | 20 A (With AC200P L) 30 A (With Solar Panel) | Lead-acid: 14.4 V LiFePO4: 14.4 V AGM / Gel: 14.7 V Calcium: 15.4 V | 48 V DC Input: 45 V to 60 V DC PV / Starter- Battery Input: 12 V to 36 VDC, 20 A Max. | IP20 | 2 kg (4.4 lbs) | 232.7 × 180.7 × 69.2 mm (9.2 × 7.1 × 2.7 in) | BLUETTI AC200P L | TBD | TBD |

