

AC60P Portable Power Station



Specifications

Model	Area	JP	US	CN	EU/AU/UK
	Battery Capacity	504Wh			
Cell Type	LiFePO4				
Net Weight	About 9.1kg/20.06lbs				
Dimensions (L*W*H)	290*205*234mm/11.42*8.07*9.21in				
Charging Temperature	0°C~40°C/32°F~104°F				
Discharging Temperature	-20°C~40°C(-20°C~30°C: 600W Max.; 30°C~40°C: 500W Max.) -4°F~104°F(-4°F~86°F: 600W Max.; 86°F~104°F: 500W Max.)				
Storage Temperature	-20°C~40°C/-4°F~104°F				
IP Grade	IP65				
Working Humidity	10%~90%				
AC Output	Power	600W in total			
	Lifting Power	1200W			
	Voltage	100VAC	120VAC	220VAC	230VAC
	Current	6A	5A	2.7A	2.6A
	Frequency	50Hz/60Hz			
DC Output	Cigarette Lighter Port*1	12VDC/10A			
	USB-A*2	5V/3A in total			
	USB-C*1	5/9/12/15/20VDC,3A;20VDC/5A (With E-Marker chip built in)			
	Wireless Charging*1	5W/7.5W/10W/15W			
AC Input	Voltage	100VAC	120VAC	220VAC	230VAC
	Max. Current	10A	10A	5A	5A
	Frequency	50Hz / 60Hz			
	UPS	Switching time ≤20ms			
	Power	600W Max.(0%-80% in 45 minutes @ 10°C~30°C/50°F~86°F)			
DC Input	Interface	DC7909			
	Power	200W/8A Max.			
	Voltage	12V~28VDC			
Expansion Port*2	Rated voltage	22.4VDC			
	Max. Input Current	30A			

Scalability



External Battery Connection	External Battery	B80P
	Capacity	806Wh
	Maximum Parrallable Battery Units	2
	Scalable Capacity	2116Wh