

Portable Power Station

Premium Series

For Every Power-Packed Adventure





Faster Charging

- -Ready to go within **1 hour** with AC Turbo Charging or PV charging
- -Tap into abundant energy of the sun through efficient PV charging.

More Compact & Powerful


- -High-density LFP battery cells for impressive capacity
- -Lifting Power for high-wattage resistive loads like hair dryers, electric kettles, etc.



1 AC

Longer Lifespan

-Reliable LFP batteries and intelligent BMS (Battery Management System) provide optimal performance and up to 10 years of lifespan.



Higher Scalability

-Modular design allows for flexible capacity ranging from 1.8kWh to 10kWh, and up to 8 tailored solutions to cater to your unique power requirements.



Smarter Control

-With the intuitive **BLUETTI App**, you can monitor your power status in real time and customize your setup effortlessly, simply manage energy in the palm of your hand.




Dynamic Design

-The Premium series products come in vibrant orange, embodying warmth, hope, and the full spirit of energy.



Applications



Home Backup

Home Backup

Workshop

Exploration

Workshop

Outdoor

Food Cart

Home Backup

Workshop

Premium 80 (AC70P)

SKU: P-AC70P-EU-GY-BL-010

10.7 kg (23.6 lbs)

314 × 210 × 256 mm

864Wh | 1,000W

 $(L \times W \times H)$ $(12.4 \times 8.2 \times 10.1 \text{ in})$ 2.000W Lifting Power power bank mode 1.670Wh (With 1 x B80P)

BLUETTI

2* AC | 1* Car Port | 2* USB-A | 2* USB-C | 1* Wireless Charger

Portable Power Station Premium Series

(L×W×H)

Lifting Power

1* AC | 1* Car Port | 2* USB-A | 1* USB-C

504Wh | 700W

(L×W×H)

Lifting Power

Expandable Capacity

1* AC | 1* Car Port | 1* USB-A | 2* USB-C | 1* Wireless Charger

504Wh | 600W

(L×W×H)

Lifting Power

2* AC | 1* Car Port | 2* USB-A | 1* USB-C | 1* Wireless Charger

230.4Wh | 300W

SKU: P-AC2P-EU-GY-BL-010

3.6 kg (7.9 lbs)

600W

250 × 150 × 180 mm

SKU: P-AC50P-EU-GY-BL-010

6.9 kg (15.2 lbs)

280 ×200 × 220 mm

SKU: P-AC60P-EU-GY-BL-010

9.6 kg(21.16 lbs)

 $(11.4 \times 8.1 \times 9.2 \text{ in})$

1.200W

290 × 205 × 234 mm

2.116Wh(With 2 x B80P)

 $(11.0 \times 7.9 \times 8.7 \text{ in})$

1.200W

Premium 20 (AC2P)

Premium 50 (AC50P)

Premium 60S (AC60P)

Battery Life Cycles 3.000+ 12V~28V.200W Max. PV Input Bidirectional Inverter IP Grade Others MPPT, UPS, APP 5 Years Warranty **Charging Time** 1.4 H (270W Max.) 1.5 H (200W Max.) 1.5 H (200W Max.) 1.4 H (270W Max.)

Battery	LiFePo ₄
Life Cycles	3,000+
PV Input	12V~28V,200W Max.
Bidirectional Inverter	\checkmark
IP Grade	/
Others	MPPT, UPS, APP
Warranty	5 Years
Charging Time	
AC	1.3 H (600W Max.)
Solar	3 H (200W Max.)
Car	3 H (200W Max.)
Generator	1.3 H (600W Max.)

Battery	LiFePo4
Life Cycles	3,000+
PV Input	12V~28V,200W Max.
Bidirectional Inverter	$\sqrt{}$
IP Grade	IP65
Others	MPPT, UPS, APP
Warranty	6 Years
Charging Time	
AC	1.3 H (600W Max.)
Solar	3 H (200W Max.)
Car	3 H (200W Max.)
Generator	1.3 H (600W Max.)

Battery	LiFePo ₄
Life Cycles	3,000+
PV Input	12V~58V,500W Max.
Bidirectional Inverter	$\sqrt{}$
IP Grade	/
Others	MPPT, UPS, APP
Warranty	5 Years
Charging Time	
AC	1.5 H (950W Max.)
Solar	2.2 H (500W Max.)
Car	4.8 H (200W Max.)
Generator	1.5 H (950W Max.)

Technology Pioneer in Clean Energy

BLUETTI BLUETTI Technology Pioneer in Clean Energy Technology Pioneer in Clean Energy

Excursion

• Emergency

Home Backup

Home Backup
 Home Backup
 Home Backup

Portable Power Station Premium Series




	Weight	17.0 kg (37.5 lbs)
ESTABLE STATE OF THE STATE OF T	Dimensions (L×W×H)	340 × 247 × 317 mm (13.4 × 9.7 × 12.5 in)
BLUETTI	Lifting Power	2,700W
	Expandable Capacity	power bank mode 2,246Wh (With 1 x B80P)

\odot	-		(((4)))

2* AC | 1* Car Port | 4* USB-A | 1* USB-C | 1* Wireless Charger

Premium 240S (AC240P) SKU: P-AC240P-EU-GY-BL-010 EAN: 6970991294877





Premium 200 V2



2,073.6Wh 2,700W		
Weight	24.2 kg (53.35 lbs)	
Dimensions (L×W×H)	350 × 250 × 323.6 mm (13.78 × 9.84 × 12.74 in)	





Premium 200 (AC200P L)





Weight	28.3 kg (62.4 lbs)
Dimensions (L×W×H)	420 × 280 × 367 mm (16.5 × 11.0 × 14.4 in)
Lifting Power	3,600W
Expandable Capacity	6,604Wh (With 2 x B210P) 7,834Wh (With 2 x B300K)

\odot				(((\$)))	0.
* AC	1* Car Port	2* USB-A	2* USB-C	2* Wireless Charger	1* R\

LiFePo ₄
3,500+
12V~60V,500W Max.
$\sqrt{}$
/
MPPT, UPS, APP
5 Years
1.5 H (1,440W Max.)
3.3 H (500W Max.)
7.2 H (200W Max.)
1.5 H (1,440W Max.)

attery	LiFePo4
e Cycles	3,500+
/Input	11V~60V,1,200W Max.
directional Inverter	$\sqrt{}$
Grade	IP65
thers	MPPT, UPS, APP
arranty	6 Years
narging Time	
	1.2 H (2,400W Max.)
olar	1.8 H (1,200W Max.)
ar	9.2 H (200W Max.)
enerator	1.2 H (2,400W Max.)

tery	LiFePo ₄
Cycles	6,000+
Input	11V~60V,1,000W Max.
irectional Inverter	\checkmark
Grade	/
ners	MPPT, UPS, APP
rranty	5 Years
arging Time	
	1.4 H (1,800W Max.)
ar	2.4 H (1,000W Max.)
•	4.2 H (560W Max.)
nerator	2 H (1,200W Max.)

Technology Pioneer in Clean Energy

Solar Panel

PV100D

SKU: P-PV100D-UG-NO-BL-010 **EAN:** 6970991296505



100W	
Weight	4.9 kg / 10.8 lbs
Dimensions	Unfolded: 1,135 × 608 mm (44.7 × 23.9 in)
	Folded: 608 × 582.5 × 35 mm (23.9 × 22.9 × 1.4 in)
Cell Type	Monocrystalline Silicon
Cell Efficiency	Up to 23.4%

Voltage at Max. Power (Vmp)	20.5 V
Current at Max. Power (Imp)	4.9A
Open Circuit Voltage (Voc)	24.6V
Short Circuit Current (Isc)	5.8A
IP Grade	IP67
Compatibility	All BLUETTI Premium Power Stations
Warranty	12 Months

PV120D

SKU: P-PV120D-EU-BK-BL-020 **EAN:** 6970991295287



120W	
Weight	5.36 kg (11.8 lbs)
Dimensions	Unfolded: 1,760 × 500 mm (69.3 × 19.7 in)
	Folded: 500 × 500 × 45 mm (19.7 × 19.7 × 1.7 in)
Cell Type	Monocrystalline Silicon
Cell Efficiency	Up to 23.4%

Voltage at Max. Power (Vmp)	20.8 V
Current at Max. Power (Imp)	6.0 A
Open Circuit Voltage (Voc)	24.6 V
Short Circuit Current (Isc)	6.6 A
IP Grade	IP67
Compatibility	All BLUETTI Premium Power Stations
Warranty	12 Months

9.7 A

24.6 V

10.8 A

IP67

All BLUETTI Premium

Power Stations

12 Months

PV200D

SKU: P-PV200D-EU-BK-BL-020 **EAN:** 6970991295270



Weight	8.14 kg (17.9 lbs)
Dimensions	Unfolded: 2,105 × 608 mm (82.8 × 23.9 in)
	Folded: 585 × 608 × 45 mm (23 × 23.9 × 1.7 in)
Cell Type	Monocrystalline Silicon
Cell Efficiency	Up to 23.4%

	,
	Current at Max. Power (Imp)
.9 lbs)	Open Circuit Voltage (Voc)
	Short Circuit Current (Isc)
8 mm .9 in)	IP Grade
× 45 mm × 1.7 in)	Compatibility
talline Silicon	Warranty
%	

Voltage at Max. Power (Vmp)

PV350D

SKU: P-PV350D-EU-BK-BL-010



350W	
Weight	14.3 kg (31.5 lbs)
Dimensions	Unfolded: 2,778 × 805 mm (109.4 × 31.6 in)
	Folded: 805 × 736 × 45 mm (31.6 × 28.9 × 1.7 in)
Cell Type	Monocrystalline Silicon
Cell Efficiency	Up to 23.4%

Voltage at Max. Power (Vmp)	37.0 V
Current at Max. Power (Imp)	9.5 A
Open Circuit Voltage (Voc)	44.0 V
Short Circuit Current (Isc)	11.4 A
IP Grade	IP67
Compatibility	Premium 80/ Premium 150/ Premium 240S/ Premium 200
Warranty	12 Months

Expansion Battery

B210P

SKU: B80P-EU-GY-BL-00

SKU: P-B210P-EU-GY-BL-010

BlueCell 300 (B300K

SKU: P-B300K-EU-GY-BL-010

EAN: 6970991294945



806Wh	
/eight	9.9 kg (21.8 lbs)
imensions	290 × 207× 204 mm (11.4 × 8.2 × 8.0 in)
otal Outlets	3
attery	LiFePO ₄
fe Cycles	3,000+

27.9 kg (61.5 lbs)

LiFePO₄

3,500+

417 × 282 × 270 mm

 $(16.4 \times 11.1 \times 10.6 \text{ in})$

29.5 kg (65.04 lbs)

LiFePO₄

525 × 327 × 209 mm (20.67 × 12.87 × 8.23 in)

2,150Wh

Total Outlets

Life Cycles

2,764.8Wh

Battery

Weight

Battery

Total Outlets

Life Cycles 4,000+

Premium 60S / Premium 80 / Compatibility Premium 150 Warranty 6 Years **Charging Time** AC Adapter 4.5 H (200W Max.) 4.5 H (200W Max.) 4.5 H (200W Max.)

IP65

IP Grade

ii Orace	11 03
Compatibility	Premium 200 / Premium 240S
Warranty	6 Years
Charging Time	
AC Adapter	4.8 H (470W Max.)
Solar	4.5 H (500W Max.)
Car	10 H (200W Max.)

IP Grade	IP20
ir Grade	IF20
Compatibility	Premium 200 / AC200MAX / AC300 / AC500
Warranty	4 Years
Charging Time	
Need to Connect	with BLUETTI Power Station

Technology Pioneer in Clean Energy

PV Optimizer (D40) SKU: A-BM-D40-UG-O9V15V4 EAN: 6970991296185

	Charging Power	Max. Output Current	Max. Output Voltage	DC Input	IP Grade	Weight	Dimensions (L × W × H)	Compatibility
CILGETTI CILGETTI	400W	20 A (With Premium 200) 30 A (With Solar Panel)	Lead-acid: 14.4 V LiFePO4: 14.4 V AGM / Gel: 14.7 V Calcium: 15.4 V	48 V DC Input: 45 V to 60 V DC PV / StarterBattery Input: 12 V to 36 VDC,20 A Max.	IP20	2.0 kg (4.4 lbs)	232.7 × 180.7 × 69.2 mm (9.2 × 7.1 × 2.7 in)	Premium 200

Charger 1 (D60L) SKU: A-CG-D60L-UG-DC EAN: 6970991296277

BLUETTI

	Power	Current	Default Voltage	Voltage Range	DC Input	IP Grade	Working Temperature	Weight	Dimensions (L × W × H)
BLUETTI	560W	10A	27V	15.0V to 56.0V (Adjustable Via APP) (With 12V Battery) 27.0V to 56.0V (Adjustable Via APP) (With 24V Battery)	12V,50A Max. (With 12V Battery) 24V, 25A Max. (With 24V Battery)	IP20	-20°C to 60°C (-4°Fto 140°F)	1.2 kg (2.65 lbs)	145 x 110 x 60 mm (5.71 × 4.33 × 2.36 in)

Runtime

		Premium 20	Premium 50	Premium 60S	Premium 80	Premium 150	Premium 240S	Premium 200 V2	Premium 200		
RV & Outdoor											
_	Phone (10Wh)	11 Times	22 Times	25 Times	43 Times	72 Times	92 Times	79 Times	116 Times		
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Portable Fridge (65W)	2.6 Hours	5.2 Hours	5.4 Hours	8.6 Hours	14.4 Hours	19.1 Hours	21.2 Hours	23.9 Hours		
	Laptop (70Wh)	2 Times	4 Times	4 Times	7 Times	11 Times	14 Times	19 Times	18 Times		
	Coffee Maker (1,500W)	-	-	-	-	0.8 Hours	1.0 Hour	1.1 Hours	1.2 Hours		

Home Backup

WiFi Router (7W)	12.7 Hours	23 Hours	23.7 Hours	31.4 Hours	52.4 Hours	77.6 Hours	4 Days	97.0 Hour
TV (60W)	2.3 Hours	5 Hours	5.8 Hours	9.2 Hours	15.4 Hours	20.5 Hours	22.7 Hours	25.6 Houi
Refrigerator (100W)	1.7 Hours	3.5 Hours	3.7 Hours	6.0 Hours	10.0 Hours	13.2 Hours	14.4 Hours	16.5 Hour

Workshop

Blender (1,400W)	-	-	-	-	0.8 Hours	1.0 Hour	1.1 Hours	1.3 Hour
 Electric Hammer (1,000W)	-	-	-	-	1.1 Hours	1.4 Hours	1.6 Hours	1.8 Hour
Circular Saw (1,800W)	-	-	-	-	0.6 Hours	0.8 Hours	0.9 Hour	1.0 Hou

Note: For reference only.



BLUETTI Technology Pioneer in Clean Energy